



RV SETUP/TAKE DOWN CHECKLISTS

LEAVING STORAGE UNIT FOR CAMPSITE

Outside

- Remember to take your time***
- Connect Batteries and Attach Covers
- Verify Propane Off
- Open door for Spouse/Partner to setup inside
- Connect Hitch to Tow vehicle
- Connect Tow Vehicle to Travel Trailer (Hitch, Chains, Stabilizer Arms, Brake Light plug)
- Raise the Jack/ Stow Yellow Blocks
- Remove Wheel Chocks (if installed)
- Inflate RV Tires (Recommended PSI)
- Inflate Tow Vehicle Tires (Recommended PSI)
- Inflate Air Bags if installed (Recommended PSI)

Inside RV

- Verify Cabin Lights and appliances work properly
- Secure Refrigerator and Freezer Doors and check thermometers after turning on previous night.
- Ensure all water faucets off
- Ensure Televisions and all items are stowed, covered, and secure.
- Lock Doors
- Return all tools to storage area and lock.

Tow Vehicle

- Tighten Sway Hitch
 - Attach/Extend and Adjust Tow Vehicle Mirror Extensions
 - Check backup camera operation
 - Check TPMS system operation
 - Clear vehicle from storage
 - Test all lights on Abbey (Brake, night driving, turn signals)
 - Test Brakes and Brake controller
 - Pray
-

RV CAMPSITE SETUP CHECKLIST

Outside

- Remember to take your time***
- Before you pull into site!
 - Check to make sure you can reach the water & electrical connections
 - Check to make sure your SLIDES have room to clear obstacles**
 - Loosen Sway Hitch**
- Unlock doors to RV
- Pull into site, set emergency brake on Tow Vehicle
- Using Manual Level - Ensure RV is level left to right (Adjust if necessary)
- Chock tires
- Disconnect trailer from tow vehicle (Hitch, Stabilizer, Brake Plug)
- Stow Hitch in RV Storage.
- Level the trailer front to back using jack.
- Connect Electrical and turn on breaker for AC power.
- Deploy stabilizer jacks
- Connect water, filter, splitter, and pressure regulator; run water clear hose
- Turn on Propane
- Ensure black/gray water valves closed; connect sewer hose
- Setup outside: Rug/Chairs/Tables/Grill/Lanterns/Other

Inside

- Check for obstacles and deploy slides
 - Extend awning - verify winds are mild to moderate only
 - Run water through faucets inside
 - Add water to toilet (2 x's and flush); Add water treatment to toilet
 - Add water treatment to bathroom sink and add water.
 - Light cooktop and verify functioning before using water heater.
 - Return all tools and totes to the storage.
 - Unsecure chairs, television and other moveable objects
 - Check Refrigerator and Freezer Temperatures
 - Grab a glass of wine or other beverage and enjoy camping
-

RV CAMPSITE TEAR DOWN CHECKLIST

Outside

- Remember to take your time***
- Check PSI of RV and Tow Vehicle Tires and add air if necessary
- Add potable water for trip (if needed)
- Put on disposable sanitary gloves
- Connect Black Tank Hose
- Connect Black Tank flush water hose
- Empty Black Tank; Flush and empty black tank until clear.
- Empty Gray Tank;
- Disconnect Black Tank Hose, Rinse, Return to storage.
- Turn off propane
- Remove sanitary gloves and wash/sanitize hands.
- Disconnect Water Splitter, Regulator, and Hose from water source and stow.

Inside

- Stow, cover, secure all moveable chairs, televisions, other furniture
- Make sure all loose items in Kitchen, Bathroom, Bedroom, Living room are secure
- Make sure everything in the refrigerator is secure (nothing heavy in door).
- Check for potential slide obstacles inside
- Retract Slides and Awning
- Turn on gas on stove, light and burn out remaining propane.
- Verify AC Power Circuit Breakers Off

Back Outside

- Disconnect power cord from electrical panel and stow cord.
- Raise Stabilizer Jacks and stow yellow Chocks
- Connect Truck to Abbey (Hitch, Chains, Stabilizer Arms, Brake Light plug)
- Raise Jack extension
- Remove Chocks on Wheels
- One more walk-through Inside Abbey (all off and stowed)
- Stow Steps
- Lock all doors and hatches
- Retract Step Handle (Rear Door)
- Last Walk around outside

Inside Tow Vehicle

- Tighten Sway Hitch
 - Attach/Extend and Adjust Tow Vehicle Mirror Extensions
 - Check backup camera operation
 - Check TPMS system operation
 - Clear vehicle from storage
 - Test all lights on Abbey (Brake, night driving, turn signals)
 - Test Brakes and Brake controller
 - Pray
-

RETURN TO STORAGE

Outside

- Remember to take your time**
- Walk RV and Tow Vehicle to ensure there was no road damage.
- Loosen Sway Hitch** (if necessary)
- Back in RV into Storage Unit; ensure sufficient space to access doors.
- Secure RV chocks on wheels
- Disconnect Truck (Hitch, Chains, Stabilizer Arms, Brake Light plug)
- Verify Propane Off

Inside RV

- Verify all items are stowed and secure
- Turn off all Lights
- Turn off all Appliances
- Verify AC Circuit Breakers Off
- Open Refrigerator and Freezer Doors to avoid mold growth
- Ensure all water faucets off
- Replace Stairs
- Ensure Handle on Rear Door in closed position
- Lock Doors

Back Outside

- Remove Batteries Covers, disconnect from RV; install trickle chargers
- Lower Stabilizer Jacks if necessary

Before Leaving Storage Unit

- Walk around RV to ensure everything is secure
- Remove Truck Mirror Extensions and place in Bag; stow in storage
- Shutoff TPMS and Rear View Camera and stow in Tow Vehicle
- Remove Hitch and stow in storage unit.
- Lock Storage Unit